


FRD Type: 31DF6

FEATURES

- * Ultra – Fast Recovery
- * Low Forward Voltage Drop
- * Low Power Loss, High Efficiency
- * High Surge Capability
- * 200 Volts thru 600 Volts Types Available

OUTLINE DRAWING



Maximum Ratings

Apporox Net Weight:1.19g

Rating	Symbol	31DF6			Unit	
Repetitive Peak Reverse Voltage	V_{RRM}	600			V	
Average Rectified Output Current	I_o	1.2	Ta=29°C *1	50Hz Half Sine Wave Resistive Load	A	
		3.0	Tl=109°C Tl:Lead Temperature			
RMS Forward Current	$I_{F(RMS)}$	4.71			A	
Surge Forward Current	I_{FSM}	45	50Hz Half Sine Wave, 1cycle, Non-repetitive		A	
Operating JunctionTemperature Range	T_{jw}	- 40 to + 150			°C	
Storage Temperature Range	T_{stg}	- 40 to + 150			°C	

Electrical/Thermal • Characteristics

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Unit
Peak Reverse Current	I_{RM}	$T_j = 25^\circ C, V_{RM} = V_{RRM}$	-	-	20	μA
Peak Forward Voltage	V_{FM}	$T_j = 25^\circ C, I_{FM} = 3 A$	-	-	1.7	V
Reverse Recovery Time	trr	$Ta = 25^\circ C, I_{FM}=3 A \ -di/dt=50A/\mu s$			35	ns
Thermal Resistance	$R_{th(j-a)}$	Junction to Ambient *1:Without Fin.	-	-	80	°C/W
	$R_{th(j-l)}$	Junction to Lead			8	

*1: Without Fin or P.C. Board

31DF6 OUTLINE DRAWING (Dimensions in mm)

