


2SC4237

(T10W80HFX)

10A NPN

OUTLINE DIMENSIONS



RATINGS

●Absolute Maximum Ratings


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T _{stg}		-55~150	℃
Junction Temperature	T _j		150	℃
Collector to Base Voltage	V _{CBO}		1200	V
Collector to Emitter Voltage	V _{CEO}		800	V
Emitter to Base Voltage	V _{EBO}		7	V
Collector Current DC	I _C		10	A
Collector Current Peak	I _{CP}		20	
Base Current DC	I _B		4	A
Base Current Peak	I _{BP}		8	
Total Transistor Dissipation	P _T	T _c = 25℃	150	W
Mounting Torque	TOR	(Recommended torque : 0.5N·m)	0.8	N·m

●Electrical Characteristics (T_c=25℃)


Item	Symbol	Conditions	Ratings	Unit
Collector to Emitter Sustaining Voltage	V _{CEO(sus)}	I _C = 0.2A	Min 800	V
Collector Cutoff Current	I _{CBO}	At rated Voltage	Max 0.1	mA
	I _{CEO}		Max 0.1	
Emitter Cutoff Current	I _{EBO}	At rated Voltage	Max 0.1	mA
DC Current Gain	h _{FE}	V _{CE} = 5V, I _C = 5A	Min 8	
	h _{FEL}	V _{CE} = 5V, I _C = 1mA	Min 5	
Collector to Emitter Saturation Voltage	V _{CE(sat)}	I _C = 5A	Max 1.0	V
Base to Emitter Saturation Voltage	V _{BE(sat)}	I _B = 1A	Max 1.5	V
Thermal Resistance	θ _{jc}	Junction to case	Max 0.83	℃/W
Transition Frequency	f _T	V _{CE} = 10V, I _C = 1A	TYP 8	MHz
Turn on Time	ton	I _C = 5A	Max 0.5	μ s
Storage Time	ts	I _{B1} = 1A, I _{B2} = 2A	Max 3.5	
Fall Time	tf	R _L = 50 Ω, V _{BB2} = 4V	Max 0.3	

2SC4237

$h_{FE} - I_C$




2SC4237 Saturation Voltage




2SC4237

Switching Time - I_C




2SC4237

Switching Time - V_{CC}




2SC4237


Switching Time - T_c




2SC4237 L-Load Switching Time - I_C



2SC4237 L-Load Switching Time - I_C (At High Temperature)




2SC4237 Transient Thermal Impedance




2SC4237

Forward Bias SOA



2SC4237 Collector Current Derating



2SC4237

Reverse Bias SOA

